

Self-pressurized Series for LN₂ Storage and Supply



Scope of Application

Liquid Nitrogen Supplement Series for LN₂ Storage and Supply incorporates the latest innovation, its unique design utilises the pressure generated from the vapourisation of a small amount liquid nitrogen to discharge LN₂ into other containers. Storage capacities range from 5 to 500 litres.

Innovative Design

- Decant Valves
- Integral Safety Mechanisms
- Liquid Storage
- 5 Year Vacuum Warranty
- Stainless Steel Construction
- Pressure Raising

Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
E-mail: inquiry@haierbiomedical.com
Website: www.haiermedical.com



Haier Biomedical
International



Haier Biomedical
International



@haiermedicalint



Haier Biomedical
International



Haier Biomedical
International

Self-pressurized Series for LN₂ Storage and Supply

Key Features

- All models are equipped with safety valves
- All welded stainless steel construction
- Rotary ring construction
- Labelled valves for easy identification
- 5 year vacuum warranty

Product Advantages

Stainless Steel Structure

Stainless steel structure can withstand the most demanding environment and ensure long-lasting security. It also provides reduced evaporation loss rate, compared with conventional welding insulation tanks.

Casters

All models have four casters for better mobility and convenient use in different occasions.

Variety of Accessories

Each Self-pressurized Series for LN₂ Storage and Supply model is equipped with a pressure valve, a drain valve, a relief valve, and a pressure gauge.

Accessories

Transfer Hose



Float-type Liquidometer



Additional Series for Liquid Nitrogen Tank

(Comparison between Standard Series and K Series)

Standard series



K series



New Functions of K Series

Digital Display Level Gauge

DLZ-300
Digital display of fluid level
Remote data transmission
function



Large diameter vent valve

Rapid relief of
over pressure
Protection of
safety valve



Pressure stabilizing valve








Stabilize fluid pressure
during auto filling












Self-pressurized Series for LN₂ Storage and Supply

Technical Parameters



Model	YDZ-5	YDZ-15	YDZ-30	YDZ-50	YDZ-100	YDZ-100K	YDZ-150
Picture							
Authentication	CE	CE	CE	CE	CE	CE	CE
Performance							
Volume of LN ₂ (L)	5	15	30	50	100	100	150
Static Evaporation (L/Day)	0.15	0.38	0.75	1	1.3	1.3	1.95
LN ₂ Output (L/Min)	≥2	≥2	≥3	≥3	≥4	≥4	≥6
Dimensions							
Height (mm)	652	771	900	1009	1179	1179	1208
Outside Diameter (mm)	354	404	454	506	606	606	706
Empty Weight (kg)	19	26	38	54	86	86	107
Full Weight (kg)	23.0	38.1	62.2	94.4	166.8	166.8	228
Shipping Weight (kg)	32	37	53	63	107	107	137
Pressure Parameters (MPa)	1. Standard working pressure 0.05, 2. Maximum working pressure 0.09, 3. First stage safety valve relief pressure 0.099, 4. Second stage safety valve release pressure 0.15, 5. Pressure gauge range 0-0.25						

Model	YDZ-200	YDZ-200K	YDZ-240K	YDZ-300	YDZ-300K	YDZ-500	YDZ-500K
Picture							
Authentication	CE	CE	CE	CE	CE	CE	CE
Performance							
Volume of LN ₂ (L)	200	200	240	300	300	500	500
Static Evaporation (L/Day)	2.4	2.4	2.9	3.3	3.3	5.5	5.5
LN ₂ Output (L/Min)	≥8	≥8	≥8	≥8	≥8	≥10	≥10
Dimensions							
Height (mm)	1288	1288	1405	1484	1484	1607	1607
Outside Diameter (mm)	758	758	758	858	858	1008	1008
Empty Weight (kg)	145	145	159	193	193	273	273
Full Weight (kg)	307	307	353	435	435	677	677
Shipping Weight (kg)	179	179	188	223	223	342	342
Pressure Parameters (MPa)	1. Standard working pressure 0.05, 2. Maximum working pressure 0.09, 3. First stage safety valve relief pressure 0.099, 4. Second stage safety valve release pressure 0.15, 5. Pressure gauge range 0-0.25						

Model	YDZ-100/1.5 (P)	YDZ-240/1.5 (P)
Picture		
Authentication	PED	PED
Performance		
Volume of LN ₂ (L)	100	240
Static Evaporation (L/Day)	1.3	2.88
Dimensions		
Height (mm)	1270	1500
Outside Diameter (mm)	606	756
Empty Weight(kg)	80	163
Full Weight (kg)	161	360
Shipping Weight (kg)	102	204
Pressure Parameters		
First stage safety valve relief pressure (Mpa/PSI)	0.15/22	
Second stage safety valve release pressure (Mpa/PSI)	0.24/35	
Pressure gauge range (Mpa/PSI)	0-1/145	
Rupture disc burst pressure (Mpa/PSI)	0.66/96	

* Static evaporation and static holding time are theoretical values. Actual evaporation and holding time are affected by usage, atmospheric conditions and manufacturing tolerances.

Self-pressurized Series for LN₂ Storage and Supply

Product List



Product	Product Model	Factory Code	Description and Accessories
Self-Pressurized Filling Tank	YDZ-5	YDZ-5-W	Includes single-layer transfusion hoses (ZG-DN10/1.5)
	YDZ-15	YDZ-15-W	Includes single-layer transfusion hoses (ZG-DN10/1.5)
	YDZ-30	YDZ-30-W	Includes single-layer transfusion hoses (ZG-DN10/1.5)
	YDZ-50	YDZ-50-W	Includes single-layer transfusion hoses (ZG-DN10/1.5)
	YDZ-100	YDZ-100-F	Includes single-layer transfusion hoses (ZG-DN10/1.5) and float-type liquidometer
	YDZ-150	YDZ-150-F	Includes single-layer transfusion hoses (ZG-DN10/1.5) and float-type liquidometer
	YDZ-200	YDZ-200-F	Includes single-layer transfusion hoses (ZG-DN10/1.5) and float-type liquidometer
	YDZ-300	YDZ-300-F	Includes single-layer transfusion hoses (ZG-DN10/1.5) and float-type liquidometer
Self-Pressurized Filling Tank	YDZ-500	YDZ-500-F	Includes single-layer transfusion hoses (ZG-DN10/1.5) and float-type liquidometer
	YDZ-100K	YDZ-100-K	Includes single-layer transfusion hoses (ZG-DN10/1.5), Digital display level gauge (DLZ-300) and pressure stabilizer. can be used for auto filling
	YDZ-200K	YDZ-200-K	Includes single-layer transfusion hoses (ZG-DN10/1.5), Digital display level gauge (DLZ-300) and pressure stabilizer. can be used for auto filling
	YDZ-240K	YDZ-240-K	Includes single-layer transfusion hoses (ZG-DN10/1.5), Digital display level gauge (DLZ-300) and pressure stabilizer. can be used for auto filling
	YDZ-300K	YDZ-300-K	Includes single-layer transfusion hoses (ZG-DN10/1.5), Digital display level gauge (DLZ-300) and pressure stabilizer. can be used for auto filling
	YDZ-320K	YDZ-320-K	Includes single-layer transfusion hoses (ZG-DN10/1.5), Digital display level gauge (DLZ-300) and pressure stabilizer. can be used for auto filling
Digital Display Level Gauge	YDZ-500K	YDZ-500-K	Includes single-layer transfusion hoses (ZG-DN10/1.5), Digital display level gauge (DLZ-300) and pressure stabilizer. can be used for auto filling
	DLZ-300 (YDZ-240K)	DLZ-300 (YDZ-240K)	Digital display real time liquid nitrogen level of self pressurized tank, low power consumption battery, wireless transmission (YDZ-240K)
	DLZ-300 (YDZ-320K)	DLZ-300 (YDZ-320K)	Digital display real time liquid nitrogen level of self pressurized tank, low power consumption battery, wireless transmission (YDZ-320K)
Float-Type Liquidometer	DLZ-300 (YDZ-500K)	DLZ-300 (YDZ-500K)	Digital display real time liquid nitrogen level of self pressurized tank, low power consumption battery, wireless transmission (YDZ-500K)
	FZ-100	FZ-100	Suitable for YDZ-100
	FZ-150	FZ-150	Suitable for YDZ-150
	FZ-200	FZ-200	Suitable for YDZ-200
	FZ-300	FZ-300	Suitable for YDZ-300
	FZ-500	FZ-500	Suitable for YDZ-500

*Haier Biomedical reserves the right to change products and specifications without prior notice.