

Smart Series (Square Racks)



Scope of Application:

The smart, IoT and cloud management system monitors temperature and liquid levels simultaneously to provide accurate and real-time information on the critical parameters to ensure ultimate sample safety.

Innovative Design

- Multiple Level of Protections
- IoT and Cloud Management
- Low Energy Consumption

- Temperature and Level Display
- High Performance Stability
- New Lock Design
- Updated Design

Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone, Qingdao, 266109, P.R. China E-mail: inquiry@haierbiomedical.com Website: www.haiermedical.com













Key Features

- 5 models from 2,400 to 6,000 cryovial capacity
- 5 years vacuum warranty
- Durable aluminium construction
- Real time monitor of temperature and level

- Cloud data storage for traceability
- Low consumption rate and high performance stability
- New lock design

Product Advantages



Colour identification for Rack handles

Rack handles are colour-coded for ease of separating storage zones and managing samples.




Double lock and double control design

The new double lock and double control design requires two people to open at the same time to ensure sample safety.



Dual monitoring respectively for temperature and liquid level

Storage temperature and liquid level are automatically monitored by a high precision controller.
Accurate and real-time information ensures samples safety.



Multilayer protection for ultimate safety

Temperature and level are monitored in real time to safeguard the storage environment. Alarms can be transmitted through email, IM and wechat.

Cloud data storage for traceability

Temperature and level data can be transmitted to Haier's IoT platform for storage. All data is traceable and stored permanently.

Low consumption rate and high performance stability

Automated manufacture ensures build quality and reliable vacuum which delivers stable and uniform temperature performance as well as low LN_2 consumption rates.



Accessories





Technical Parameters

Model	YDS-65-216	YDS-95-216	YDS-115-216	YDS-145-216	YDS-145-216
	3	1			
Picture	Note: YO S d 5-2 1-6	Han Y015-59-5165	400 100 11 6 J 15	Manus region to the First	new conservation of
Authentication	CE	CE	CE	CE	CE
Maximum Storage Volume					
No. of canister	6	6	6	6	6
2ml Storage Vials (100/box)	2400	3000	3600	4800	6000
Layers in Rack	4	5	6	8	10
5ml Storage Vials (81/box)	972	972	1458	1944	2430
Layers in Rack	2	2	3	4	5
Function					
Liquid Nitrogen Volume (L)	65	95	115	145	175
Static Evapouration Rate* (L/Day)	0.78	0.94	0.94	0.94	0.95
Static Holding Time** (Day)	83	101	122	154	184
Dimensions					
Neck Opening (mm)	216	216	216	216	216
Overall Height (mm)	760	825	895	995	1110
Overall Diameter (mm)	681	681	681	681	681
Empty Weight (kg)	41	44	48	53	58
Full Weight (kg)	108	121	141	171	199.5
Shipping Weight (kg)	65.5	69.2	75.9	85.2	94.5

^{*} Static evapouration and static holding time are theoretical values. Actual evapouration and holding time are affected by usage, atmospheric conditions and manufacturing tolerances.

Product List

Model	Product	Product Model	Factory Code	Description and Accessories
YDS-65-216	Smart Liquid Nitrogen Container (Smart Series)	YDS-65-216	YDS-65-216-FZH	Includes 6 racks(4-tier), cryoboxes(9*9), lockable cap, roller base is optional
YDS-95-216	Smart Liquid Nitrogen Container (Smart Series)	YDS-95-216	YDS-95-216-FZH	Includes 6 racks(5-tier), cryoboxes(9*9), lockable cap, roller base is optional
YDS-115-216	Smart Liquid Nitrogen Container (Smart Series)	YDS-115-216	YDS-115-216-FZH	Includes 6 racks(6-tier), cryoboxes(9*9), lockable cap, roller base is optional
YDS-145-216	Smart Liquid Nitrogen Container (Smart Series)	YDS-145-216	YDS-145-216-FZH	Includes 6 racks(8-tier), cryoboxes(9*9), lockable cap, roller base is optional
YDS-175-216	Smart Liquid Nitrogen Container (Smart Series)	YDS-175-216	YDS-175-216-FZH	Includes 6 racks(10-tier), cryoboxes(9*9), lockable cap, roller base is optional
	Roller Base	YSC-685-5W	YSC-685-5W	Suitable for all 65L-175L aluminium tank, equipped with 5 universal wheels

 $\hbox{^*Haier Biomedical reserves the right to change products and specifications without prior notice.}$

^{**} Static Holding Time: the amount of days it takes for all of the LN to evapourate out after container is filled with liquid nitrogen to pre-cool and reach thermal equilibrium and the liquid nitrogen filling rate reaches 100% under standard atmospheric condition.